

Trilinea Series™

Catalog Number

Type

Project Name

Rectangular

Elliptical

Obround



SPECIFICATIONS

Housing

Two-piece .080" thick extruded aluminum. Die-cast aluminum end plates are secured with no visible fasteners. Standard lengths are 4', 8' and 12'. Provisions may be made for continuous rows of any length.

Finish

Standard and premium finishes are baked powder coat electrostatically applied (2.0 mil minimum thickness) to assure aesthetics and durability.

Indirect Optical Controls

- (OP) Open top 60%↑ 40%↓
- (TP4) Transmittive optical panel 40%↑ 60%↓
- (TP2) Transmittive optical panel 20%↑ 80%↓
- (SP) Solid aluminum panel 0%↑ 100%↓

Direct Optical Controls

- (PB) 1 1/2" deep semi-specular aluminum parabolic baffle with blades on 4" centers
- (PBW) 1 1/2" deep white aluminum parabolic baffle with blades on 4" centers

Reflectors

Die-formed from .020" thick high reflectance specular aluminum.

Ballast

Standard ballasts for T8 lamps are UL/CUL listed, Class P, HPF, electronic, universal 120/277volt, instant start with <10% THD.

Circuitry

All fixtures are factory pre-wired for a single circuit. Provision for multiple switching/circuiting is optional.

Wiring

All fixtures intended for continuous rows are provided with factory installed quick-connect wiring.

Controls


Contact factory for control by Occupancy Sensors, Photo Controls and Daylight Harvesting.

Certification


All fixtures are UL/CUL listed for use in "Dry Applications". "Damp Location" is optional.

TRP02-T8


Indirect/Direct & Direct (T8 Lamps)



TRP02-E
8 5/8" x 3 1/2"



TRP02-O
8" x 3 1/2"



TRP02-R
8" x 3 1/2"

	Standard Lengths: 4', 8' and 12'	Mounting W = Wall				
Series TRP02						
TRP02-0-12-W-TP4/PB-F01M-V-T8-[]						
Housing Style	Indirect Optical Controls	Direct Optical Controls	Standard Finishes	Voltage	Lamp Type	Options
E Elliptical	OP 60% ↑ 40% ↓	PB Semi-Specular Parabolic Baffle	F01M Matte White	120	T8	SS-L/R (Common Neutral Utilized)
O Obround	TP4 40% ↑ 60% ↓	PBW White Parabolic Baffle	Premium Finishes F01G Gloss White	277		EMCKT (635-700 Lumens)
R Rectangular	TP2 20% ↑ 80% ↓		F02 Ivory	347		NLCKT (Separate Night Light Circuit)
	SP 0% ↑ 100% ↓		F03 Stonewash			EBPL (Emergency Battery Pack)
			F04 Camel			EBPH (Emergency Battery Pack)
			F05 Gray Day			
			F06 Pebble Beach			
			F07 Steel			
			F08 Gray Seal			
			F09 Mocha			
			F10 Bronzed			
			F11 Black			
			F12 Ultrasonic Clear			
			F13 Merlot			
			F14 Red Skies			
			F15 Lemon			
			F16 Forest Hunter			
			F17 Olive			
			F18 Khaki			
			F19 Heather Green			
			F20 Blue Print			
			F21 Reflex Blue			
			F22 Navy			
			FCC Custom Color			



Precision Architectural Lighting 4830 Timber Creek Drive Houston, Texas 77017
Tel 713.946.4343 Fax 713.946.4441 www.pal-lighting.com

Tel 713.946.4343 Fax 713.946.4441 www.pal-lighting.com