

System
Solutions

AS350™ SERIES




Precision
Architectural
Lighting




AS350 SERIES™


WALL



AS350-HO-W
AS350-MO-W
WALL MOUNT




AS350-HO-FW
AS350-MO-FW
FLUSH WALL MOUNT
(ADA COMPLIANT)




AS350-HO-DW
AS350-MO-DW
DIAMOND WALL MOUNT

CEILING



AS350-HO-J
AS350-MO-J
CEILING MOUNT (FLUSH)



AS350-HO-DJ
AS350-MO-DJ
DIAMOND CEILING MOUNT

FEATURES:

- High efficacy ratings (as high as 124 Lms/W) and multiple mounting options combine to make the AS350 an extremely versatile fixture.
- Available with 0-10 volt dimming and Tunable White options.
- Ideal for applications such as bathrooms, stairwells, and healthcare facilities.



WALL MOUNT:

Series	Nominal Lengths:	Mounting	Voltage
AS350	4', 8' and 12' For continuous rows of 12' or longer, specify nominal row length in 1' increments.	W = Wall FW = Flush Wall DW = Diamond Wall	120 277 347 UNV
AS350-HO-K40-80-4'-W-LOH-F01M-120-[]			
Lumen Output - Wall and Flush Wall	CCT	CRI	Optical Control
HO - High Output *3170 Total Lumens - 114 Lm/W	K30 3000 Kelvin	80	LOH LED Optimized Acrylic Lens
MO - Medium Output *1967 Total Lumens - 116 Lm/W	K35 3500 Kelvin	90	
Lumen Output - Diamond Wall	K40 4000 Kelvin		
HO - High Output *3389 Total Lumens - 123 Lm/W	TW - (Tunable White) (2700K - 6500K)		
MO - Medium Output *2094 Total Lumens - 124 Lm/W			
*Lumen ratings per 4' section (3500K)			
Standard Finishes	Options		
F01M Matte White	NLCKT Night Light Circuit (Common Neutral)	Dim1 Dimming - to 1%	FS Fused Drivers
Premium Finishes	EMCKT Emergency Circuit (Separate Hot & Neutral)	Dim0 Dimming - to .1% (Dark)	DL Damp Location
F01G Gloss White	EBPLST Self-Test. EM Battery Pack (6 Watt) *N/A for 2' & 3'	DALI DALI Protocol Driver - (TW)	DMX DMX Protocol Driver - (TW)
F02 Ivory	EBPHST Self-Test. EM Battery Pack (10 Watt) *N/A for 2' & 3'	0-10V/TW 0 - 10V Driver - (TW)	
F03 Stonewash			
F04 Camel			
F05 Gray Day			
F06 Pebble Beach			
F07 Steel			
F08 Gray Seal			
F09 Mocha			
F10 Bronzed			
F11G Gloss Black			
F11M Matte Black			
F12 Ultrasonic Clear			
F13 Merlot			
F14 Red Skies			
F15 Lemon			
F16 Forest Hunter			
F20 Blue Print			
F21 Reflex Blue			
F22 Navy			
FCC Custom Color			

CEILING MOUNT:

Series	Nominal Lengths:	Mounting	Voltage
AS350	4', 8' and 12' For continuous rows of 12' or longer, specify nominal row length in 1' increments.	J = Ceiling (Flush) DW = Diamond Ceiling	120 277 347 UNV
AS350-HO-K40-80-4'-J-LOH-F01M-120-[]			
Lumen Output - Ceiling (Flush)	CCT	CRI	Optical Control
HO - High Output *3170 Total Lumens - 114 Lm/W	K30 3000 Kelvin	80	LOH LED Optimized Acrylic Lens
MO - Medium Output *1967 Total Lumens - 116 Lm/W	K35 3500 Kelvin	90	
Lumen Output - Diamond Ceiling	K40 4000 Kelvin		
HO - High Output *3390 Total Lumens - 123 Lm/W	TW - (Tunable White) (2700K - 6500K)		
MO - Medium Output *2086 Total Lumens - 123 Lm/W			
*Lumen ratings per 4' section (3500K)			
Standard Finishes	Options		
F01M Matte White	NLCKT Night Light Circuit (Common Neutral)	Dim1 Dimming - to 1%	FS Fused Drivers
Premium Finishes	EMCKT Emergency Circuit (Separate Hot & Neutral)	Dim0 Dimming - to .1% (Dark)	DL Damp Location
F01G Gloss White	EBPLST Self-Test. EM Battery Pack (6 Watt) *N/A for 2' & 3'	DALI DALI Protocol Driver - (TW)	DMX DMX Protocol Driver - (TW)
F02 Ivory	EBPHST Self-Test. EM Battery Pack (10 Watt) *N/A for 2' & 3'	0-10V/TW 0 - 10V Driver - (TW)	
F03 Stonewash			
F04 Camel			
F05 Gray Day			
F06 Pebble Beach			
F07 Steel			
F08 Gray Seal			
F09 Mocha			
F10 Bronzed			
F11G Gloss Black			
F11M Matte Black			
F12 Ultrasonic Clear			
F13 Merlot			
F14 Red Skies			
F15 Lemon			
F16 Forest Hunter			
F20 Blue Print			
F21 Reflex Blue			
F22 Navy			
FCC Custom Color			



Precision Architectural Lighting

Tel 713.946.4343 Fax 713.946.4441 www.pal-lighting.com

4830 Timber Creek Drive Houston, Texas 77017



Made in America