Microlinea Suspended Series 2, 3 & 5

Lighted Corner Specifications - LED

S P E C I F I C A T I O N S

Microlinea Suspended Series 2 - LED
Lighted 90 Degree corner
(Direct Only or Indirect/Direct)

Fixture Length as Specified · 24 11/16" · 24 1/16" · Fixture Length as Specified

Extruded aluminum 90° mitered corners are available when surface or pendant mounted patterns are desired. Series 2, Series 3 and Series 5 corners are available in nominal 2' x 2' long continuously lighted configurations.

*See corresponding Microlinea Suspended LED catalog pages for fixture specifications.

5 Year Limited Warranty - LED Boards & Drivers

Microlinea Suspended Series 3 - LED
Lighted 90 Degree corner
(Direct Only or Indirect/Direct)

Fixture Length as Specified · 25 5/8" · 24 1/8" · Fixture Length as Specified

Microlinea Suspended Series 5 - LED
Lighted 90 Degree corner
(Direct Only or Indirect/Direct)

Fixture Lgth as Specified · 26 9/16" · 25 1/8" · Fixture Length as Specified

H O W   T O   O R D E R

Sample Catalog Number: **MLS3-I/D - HO / HO - K40 - 80 - L90 - CN - DC / LOH - F01M - 120 - DIM1 - OPTIONS**

MLS2, MLS3, & MLS5 Series Corners
MLS2-D- Direct, **MLS3-D** - Direct, **MLS5-D** - Direct
MLS2-I/D - Ind./Dir, **MLS3-I/D** - Ind./Dir, **MLS5-I/D** - Ind./Dir.
Indirect Lumen Outputs:
MLS2-D, MLS3-D, MLS5-D: XX
MLS2-I/D, MLS3-I/D, MLS5-I/D: HO - High Output
MO- Medium Output
CO - Custom Output
Direct Lumen Outputs:
MLS2-D, MLS3-D, MLS5-D: HO - High Output
MLS2-I/D, MLS3-I/D, **MO**- Medium Output
MLS5-I/D **CO** - Custom Output
CCT: **K30** - 3000K, **K35** - 3500K, **K40** - 4000K, **TW**- Tunable White (2700 - 6500K)
CRI: **80** (Standard), **90** (Optional)
Corner Type: **90 Degree Lit - Suspended or Ceiling Mount**
Mountings: **CN** = Cable Assy. (Non-Tbar) - Fully Adjustable (36" Std)   **J** = Ceiling Mount
P = Rigid Stem Assy. (Up to 48" Std) - Direct Only   **P** = Swivel Stem Assy. (Up to 48" Std) - Direct Only
Indirect Optical Control: **OP** = Open   **DC** = Dust Cover   **XX** = Direct Only
Direct Optical Control: **LOH** = LED Optimized Acrylic Snap-in Lens

Standard Finish: **F01M** Matte White   Premium Finishes:

	F01G Gloss White	**F06** Pebble Beach	**F11G** Gloss Black	**F15** Lemon
	F02 Ivory	**F07** Steel	**F11M** Matte Black	**F16** Forest Hunter
	F03 Stonewash	**F08** Gray Seal	**F12** Ultrasonic Clear	**F20** Blue Print
	F04 Camel	**F09** Mocha	**F13** Merlot	**F21** Reflex Blue
	F05 Gray Day	**F10** Bronzed	**F14** Red Skies	**F22** Navy
				FCC Custom Color

Voltage: **120V, 277V, 347V or UNV** (Universal Voltage)
Dimming: **DIMX** = Standard Driver - no Dimming   **DIM1** = Standard Driver wired for Dimming - 100% to 1%   **DIM0** = Optional Driver with Available Dimming - 100% to 0%
Options: **NLCKT** = Night-Light Circuit (Common Neutral)   **EMCKT** = Emergency Circuit (Separate Hot & Neutral)   **EBPHST** = Self-Testing Emergency Battery Pack (10 Watt)
DALI = DALI Protocol Driver (Tunable White)   **DMX** = DMX Protocol Driver (Tunable White)   **0-10/TW** = 0-10V Protocol Driver (Tunable White)   **FS** = Fused Drivers